

Drywall Tools

Black vinyl cushion grips with handle stops.

Punch Lock Stud Crimper

Secures any width Stud and Runner without screws or other fasteners.

Unique Punch and Die are easily replaceable



Powerful compound leverage design

Maximum capacity 22 gauge stud and runner.



Enlarged Crimp Connection



PL1

Compound leverage increases mechanical advantage nearly 7 to 1. Simply squeeze handles together with one hand while holding stud in place. A unique punch and die shape creates a rectangular crimp, bending over thicknesses of channel and stud at the same time to form a sturdy bond. Crimp is always the proper strength and resists stress from any angle. Spring return handles snap the punch back in a ready position to go on to the next stud or fastening point. Lightweight and compact size allows the user to work overhead or in tight quarters with ease. Tool fits inside the smallest stud and runner. Punch and dies are constructed from high quality tool steel and are easily replaceable. Body of tool consists of an aluminum die cast 'C' frame and rust resistant, nickel plated steel handles and parts. Tool also features non-slip vinyl grips with hand stops for added comfort and resistance to elements.

CATALOG NUMBER	DESCRIPTION	THROAT DEPTH IN. (MM)	CAPACITY GALVANIZED STEEL 22 GAUGE IN. (MM)	NET WT. OZ. (G)
PL1	Punch Lock/ Stud Crimper	1-1/2 (38.1)	.034 (0.86)	16 (454)

REPLACEMENT PARTS

PLD1	Replacement Punch and Die
------	---------------------------

TOOL SPECIFICATIONS

PUNCH / FRAME	VARIABLE LEVERAGE RATIO HIGH/LOW THROUGHOUT STROKE
Tool Steel Punch w/Cast Aluminum Frame	Shear Action (Punch)

Compound Leverage Channel Shear



SRC24A

Compound leverage shear cuts through 20 gauge metal studs and runner faster, easier and more economically than any other tool on the market. Shear completes cut in one easy stroke without deforming metal channel. Die assembly assures that cutting action is clean and precise. Hollow ground hardened steel blade can be resharpened or replaced. A 36" (91 cm) long handle provides additional leverage making cutting with this shear almost effortless. Lightweight and portable enough to be where you want it, when you want it. Model SRC24A cuts 3 basic channel sizes 1-5/8, 2-1/2 & 3-5/8" (41.3, 63.5 and 92.1 mm) stud and accommodating runners. Shear features rugged all steel and bolt construction. Handle has red vinyl comfortable grips.

CATALOG NUMBER	CAPACITY GALVANIZED STEEL 20 GAUGE IN. (CM)	CUTS BOTH STUD & RUNNER SIZES IN. (CM)	HEIGHT IN. (CM)	LENGTH IN. (CM)	NET WT. LBS. (KG)
SRC24A	0.40 (1.02)	1-5/8, 2-1/2 & 3-5/8 (4, 7, & 9)	8 (20)	36 (91)	23.00 (10.43)

REPLACEMENT BLADE

CATALOG NUMBER	DESCRIPTION
10627	One replacement blade and two spacers. Field replacement.

RELATED ITEMS

Ceiling Grid Punch
No. CGP See page 83

